



**M1 125 - SINGLE-PHASE
TRANSFORMER 400/230V ±5% -
ELECTROSTATIC SHIELD - 125VA - IP00**



SKU: 22194
Référence technique: 09M19FDF1000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : EN 61558-2-1
Power : 125 VA
Primary voltage : 400V
Secondary voltage : 230V
:
Protection : IP00
Version : with electrostatic shield & regulation tabs ±5%
Inrush current : less than or equal to 25 In
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 7 W
Load losses : 10,7 W
Voltage drop : 7,9 %
UCC : 6,5 %
Efficiency : 87,6 %

DIMENSIONS:

Dimensions (A x B x H) : 99 x 100 x 95 mm
Mounting centres (a x b) : 80 x 65 mm
Mounting diameter (ø) : 6x11 mm
Weight : 2,7 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 1 x 1A
:
Secondary 230V (gG fuse(s)) : 1 x 0,5A
Secondary 230V (C circuit breaker(s)) : 1 x 0,5A

OPTIONS:

Tropicalization