




M1 1250 - ON REQUEST SINGLE-PHASE TRANSFORMER 1250VA - IP00



SKU: M11250_Specific
 Référence technique: 09B32...



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : single-phase
 Certification(s) : EN 60076
 Power : 1250 VA
 Primary voltage : max. 1000V
 Secondary voltage : max. 1000V
 :
 Protection : IP00
 Version : Transformer (specific)
 Inrush current : less than or equal to 25 In
 Heatings : F (IEC 60085)
 Max. ambient T° : 40°C
 No load losses : 38 W
 Load losses : 63 W
 Voltage drop : 4,8 %
 UCC : 3,6 %
 Efficiency : 92,6 %

DIMENSIONS:

Dimensions (A x B x H) : 153 x 170 x 135 mm
 Mounting centres (a x b) : 125 x 141 mm
 Mounting diameter (ø) : 9x18 mm
 Weight : 14 kg

PROTECTION(S) RECOMMANDÉE(S):

:
 Other voltages : N.C.

OPTIONS:

Electrostatic shield
 Thermal sensors (PTC, PT100, Twin-blades)
 Regulation tabs
 Dual primary
 Inrush current, frequency, heating, ambient temperature, specific altitude
 Tropicalization