


## M1 1600 - ON REQUEST SINGLE-PHASE TRANSFORMER 1600VA - IP00



SKU: M11600\_Specific  
 Référence technique: 09B34...

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : single-phase  
 Certification(s) : EN 60076  
 Power : 1600 VA  
 Primary voltage : max. 1000V  
 Secondary voltage : max. 1000V  
 :  
 Protection : IP00  
 Version : Transformer (specific)  
 Inrush current : less than or equal to 25 In  
 Heatings : F (IEC 60085)  
 Max. ambient T° : 40°C  
 No load losses : 44 W  
 Load losses : 70 W  
 Voltage drop : 4,2 %  
 UCC : 3,4 %  
 Efficiency : 93,3 %

### DIMENSIONS:

Dimensions (A x B x H) : 187 x 152 x 167 mm  
 Mounting centres (a x b) : 155 x 115 mm  
 Mounting diameter (Ø) : 8x16 mm  
 Weight : 17,6 kg

### PROTECTION(S) RECOMMANDÉE(S):

:  
 Other voltages : N.C.

### OPTIONS:

Electrostatic shield  
 Thermal sensors (PTC, PT100, Twin-blades)  
 Regulation tabs  
 Dual primary  
 Inrush current, frequency, heating, ambient temperature, specific altitude  
 Tropicalization