




**M1 200 - SINGLE-PHASE
TRANSFORMER 400/230V ±5% -
ELECTROSTATIC SHIELD - 200VA - IP00**



SKU: 22224
Référence technique: 09M22FDF1000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : EN 61558-2-1
Power : 200 VA
Primary voltage : 400V
Secondary voltage : 230V
:
Protection : IP00
Version : with electrostatic shield & regulation tabs ±5%
Inrush current : less than or equal to 25 In
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 9,2 W
Load losses : 16 W
Voltage drop : 7,3 %
UCC : 6 %
Efficiency : 88,9 %

DIMENSIONS:

Dimensions (A x B x H) : 99 x 115 x 104 mm
Mounting centres (a x b) : 80 x 80 mm
Mounting diameter (ø) : 6x11 mm
Weight : 3,9 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 1 x 1A
:
Secondary 230V (gG fuse(s)) : 1 x 1A
Secondary 230V (C circuit breaker(s)) : 1 x 1A

OPTIONS:

Tropicalization