




**M1 250 - SINGLE-PHASE
 TRANSFORMER 400/230V ±5% -
 ELECTROSTATIC SHIELD - 250VA - IP00**



SKU: 22234
 Référence technique: 09M23FDF1000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : single-phase
 Certification(s) : EN 61558-2-1
 Power : 250 VA
 Primary voltage : 400V
 Secondary voltage : 230V
 :
 Protection : IP00
 Version : with electrostatic shield & regulation tabs ±5%
 Inrush current : less than or equal to 25 I_n
 Heatings : B (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 10,8 W
 Load losses : 18 W
 Voltage drop : 6,8 %
 UCC : 5,6 %
 Efficiency : 89,6 %

DIMENSIONS:

Dimensions (A x B x H) : 122 x 110 x 109 mm
 Mounting centres (a x b) : 100 x 78 mm
 Mounting diameter (ø) : 7x12 mm
 Weight : 4,4 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 1 x 1,6A
 :
 Secondary 230V (gG fuse(s)) : 1 x 1,25A
 Secondary 230V (C circuit breaker(s)) : 1 x 1,25A

OPTIONS:

Tropicalization