




**M1 2500 - SINGLE-PHASE
TRANSFORMER 400/230V ±5% -
ELECTROSTATIC SHIELD - 2,5KVA -
IP00**



SKU: 22364

Référence technique: 09B36FDF1000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : EN 60076
Power : 2,5 kVA
Primary voltage : 400V
Secondary voltage : 230V
:
Protection : IP00
Version : Transformer (electrostatic shield & regulation tabs ±5%)
Inrush current : less than or equal to 25 I_n
Heatings : F (IEC 60085)
Max. ambient T° : 40°C
No load losses : 60 W
Load losses : 89 W
Voltage drop : 3,4 %
UCC : 2,9 %
Efficiency : 94,4 %

DIMENSIONS:

Dimensions (A x B x H) : 187 x 185 x 167 mm
Mounting centres (a x b) : 155 x 145 mm
Mounting diameter (∅) : 8x16 mm
Weight : 23,9 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 1 x 16A
:
Secondary 230V (gG fuse(s)) : 1 x 10A
Secondary 230V (C circuit breaker(s)) : 1 x 10A

OPTIONS:

Tropicalization