



M1 2500 - ON REQUEST SINGLE-PHASE TRANSFORMER 2,5KVA - IP00



SKU: M12500_Specific
Référence technique: 09B36...

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : EN 60076
Power : 2,5 kVA
Primary voltage : max. 1000V
Secondary voltage : max. 1000V
:
Protection : IP00
Version : Transformer (specific)
Inrush current : less than or equal to 25 In
Heatings : F (IEC 60085)
Max. ambient T° : 40°C
No load losses : 60 W
Load losses : 89 W
Voltage drop : 3,4 %
UCC : 2,9 %
Efficiency : 94,4 %

DIMENSIONS:

Dimensions (A x B x H) : 187 x 185 x 167 mm
Mounting centres (a x b) : 155 x 145 mm
Mounting diameter (Ø) : 8x16 mm
Weight : 23,9 kg

PROTECTION(S) RECOMMANDÉE(S):

:
Other voltages : N.C.

OPTIONS:

Electrostatic shield
Thermal sensors (PTC, PT100, Twin-blades)
Regulation tabs
Dual primary
Inrush current, frequency, heating, ambient temperature, specific altitude
Tropicalization