




M1 315 - SINGLE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - ELECTROSTATIC SHIELD - 315VA - IP00



SKU: 22244
 Référence technique: 09M25FDF1000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : single-phase
 Certification(s) : EN 61558-2-1
 Power : 315 VA
 Primary voltage : 400V
 Secondary voltage : 230V
 :
 Protection : IP00
 Version : with electrostatic shield & regulation tabs $\pm 5\%$
 Inrush current : less than or equal to 25 In
 Heatings : B (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 13 W
 Load losses : 21 W
 Voltage drop : 6,3 %
 UCC : 5,2 %
 Efficiency : 90,2 %

DIMENSIONS:

Dimensions (A x B x H) : 122 x 115 x 109 mm
 Mounting centres (a x b) : 100 x 83 mm
 Mounting diameter (\emptyset) : 7x12 mm
 Weight : 5 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 1 x 1,6A
 :
 Secondary 230V (gG fuse(s)) : 1 x 1,6A
 Secondary 230V (C circuit breaker(s)) : 1 x 1,6A

OPTIONS:

Tropicalization