



**M1 400 - SINGLE-PHASE
TRANSFORMER 230/230V ±5% -
ELECTROSTATIC SHIELD - 400VA - IP00**



SKU: 21264
Référence technique: 09M26DDF1000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : EN 61558-2-1
Power : 400 VA
Primary voltage : 230V
Secondary voltage : 230V
:
Protection : IP00
Version : with electrostatic shield & regulation tabs ±5%
Inrush current : less than or equal to 25 In
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 15 W
Load losses : 28 W
Voltage drop : 6,5 %
UCC : 4,8 %
Efficiency : 90,3 %

DIMENSIONS:

Dimensions (A x B x H) : 122 x 120 x 109 mm
Mounting centres (a x b) : 100 x 92 mm
Mounting diameter (ø) : 7x12 mm
Weight : 5,5 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 4A
Primary 230V (D circuit breaker) : 1 x 4A
:
Secondary 230V (gG fuse(s)) : 1 x 2A
Secondary 230V (C circuit breaker(s)) : 1 x 2A

OPTIONS:

Tropicalization