



## M1 5000 - SINGLE-PHASE TRANSFORMER 230/230V $\pm 5\%$ - ELECTROSTATIC SHIELD - 5KVA - IP00



SKU: 21404  
Référence technique: 09B40DDF1000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : single-phase  
Certification(s) : EN 60076  
Power : 5 kVA  
Primary voltage : 230V  
Secondary voltage : 230V  
:  
Protection : IP00  
Version : Transformer (electrostatic shield & regulation tabs  $\pm 5\%$ )  
Inrush current : less than or equal to 25 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 40°C  
No load losses : 97 W  
Load losses : 150 W  
Voltage drop : 2,9 %  
UCC : 3,5 %  
Efficiency : 95,3 %

### DIMENSIONS:

Dimensions (A x B x H) : 240 x 225 x 240 mm  
Mounting centres (a x b) : 200 x 159 mm  
Mounting diameter ( $\varnothing$ ) : 12x31 mm  
Weight : 39 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 50A  
Primary 230V (D circuit breaker) : 1 x 50A  
:  
Secondary 230V (gG fuse(s)) : 1 x 20A  
Secondary 230V (C circuit breaker(s)) : 1 x 20A

### OPTIONS:

Tropicalization