





M1 5000 - SINGLE-PHASE TRANSFORMER 400/230V - ELECTROSTATIC SHIELD - 5KVA - IP00



SKU: 22402

Référence technique: 09B40FD01000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : single-phase
 Certification(s) : EN 60076
 Power : 5 kVA
 Primary voltage : 400V
 Secondary voltage : 230V
 :
 Protection : IP00
 Version : Transformer (electrostatic shield)
 Inrush current : less than or equal to 25 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 40°C
 No load losses : 97 W
 Load losses : 150 W
 Voltage drop : 2,9 %
 UCC : 3,5 %
 Efficiency : 95,3 %

DIMENSIONS:

Dimensions (A x B x H) : 240 x 225 x 240 mm
 Mounting centres (a x b) : 200 x 159 mm
 Mounting diameter (ø) : 12x31 mm
 Weight : 39 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 1 x 25A
 :
 Secondary 230V (gG fuse(s)) : 1 x 20A
 Secondary 230V (C circuit breaker(s)) : 1 x 20A

OPTIONS:

Tropicalization