





M1 5000 - SINGLE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - ELECTROSTATIC SHIELD - 5KVA - IP00



SKU: 22404
Référence technique: 09B40FDF1000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : EN 60076
Power : 5 kVA
Primary voltage : 400V
Secondary voltage : 230V
:
Protection : IP00
Version : Transformer (electrostatic shield & regulation tabs $\pm 5\%$)
Inrush current : less than or equal to 25 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 97 W
Load losses : 150 W
Voltage drop : 2,9 %
UCC : 3,5 %
Efficiency : 95,3 %

DIMENSIONS:

Dimensions (A x B x H) : 240 x 225 x 240 mm
Mounting centres (a x b) : 200 x 159 mm
Mounting diameter (\varnothing) : 12x31 mm
Weight : 39 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 1 x 25A
:
Secondary 230V (gG fuse(s)) : 1 x 20A
Secondary 230V (C circuit breaker(s)) : 1 x 20A

OPTIONS:

Tropicalization