




## M1 500 - ON REQUEST SINGLE-PHASE TRANSFORMER 500VA - IP00



SKU: M1500\_Specific  
 Référence technique: 09M27...

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : single-phase  
 Certification(s) : EN 61558-2-1  
 Power : 500 VA  
 Primary voltage : max. 1000V  
 Secondary voltage : max. 1000V  
 :  
 Protection : IP00  
 Version : specific  
 Inrush current : less than or equal to 25 In  
 Heatings : B (IEC 60085)  
 Max. ambient T° : 35°C  
 No load losses : 18 W  
 Load losses : 31 W  
 Voltage drop : 5,9 %  
 UCC : 4,4 %  
 Efficiency : 91,1 %

### DIMENSIONS:

Dimensions (A x B x H) : 122 x 130 x 109 mm  
 Mounting centres (a x b) : 100 x 102 mm  
 Mounting diameter (ø) : 7x12 mm  
 Weight : 6,4 kg

### PROTECTION(S) RECOMMANDÉE(S):

:  
 Other voltages : N.C.

### OPTIONS:

Electrostatic shield  
 Thermal sensors (PTC, PT100, Twin-blades)  
 Regulation tabs  
 Dual primary  
 Inrush current, frequency, heating, ambient temperature, specific altitude  
 Tropicalization