





## M1 630 - ON REQUEST SINGLE-PHASE TRANSFORMER 630VA - IP00



SKU: M1630\_Specific  
 Référence technique: 09M28...



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : single-phase  
 Certification(s) : EN 61558-2-1  
 Power : 630 VA  
 Primary voltage : max. 1000V  
 Secondary voltage : max. 1000V  
 :  
 Protection : IP00  
 Version : specific  
 Inrush current : less than or equal to 25 In  
 Heatings : B (IEC 60085)  
 Max. ambient T° : 35°C  
 No load losses : 19 W  
 Load losses : 40 W  
 Voltage drop : 5,9 %  
 UCC : 5 %  
 Efficiency : 91,5 %

### DIMENSIONS:

Dimensions (A x B x H) : 153 x 120 x 135 mm  
 Mounting centres (a x b) : 125 x 91 mm  
 Mounting diameter (Ø) : 9x18 mm  
 Weight : 7,8 kg

### PROTECTION(S) RECOMMANDÉE(S):

:  
 Other voltages : N.C.

### OPTIONS:

Electrostatic shield  
 Thermal sensors (PTC, PT100, Twin-blades)  
 Regulation tabs  
 Dual primary  
 Inrush current, frequency, heating, ambient temperature, specific altitude  
 Tropicalization