




M1P 3150 - ON REQUEST SINGLE-PHASE TRANSFORMER 3,15KVA - IP21



SKU: M1P3150_Specific
 Référence technique: 10B38...

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : single-phase
 Certification(s) : EN 60076
 Power : 3,15 kVA
 Primary voltage : max. 1000V
 Secondary voltage : max. 1000V
 :
 Protection : IP21-IK08
 Version : Transformer (specific)
 Inrush current : less than or equal to 25 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 40°C
 No load losses : 60 W
 Load losses : 145 W
 Voltage drop : 4,4 %
 UCC : 5,5 %
 Efficiency : 93,9 %

DIMENSIONS:

Dimensions (A x B x H) : 380 x 370 x 530 mm
 Mounting centres (a x b) : 200 x 340 mm
 Mounting diameter (ø) : 11x22 mm
 Weight : 36 kg

PROTECTION(S) RECOMMANDÉE(S):

:
 Other voltages : N.C.

OPTIONS:

Electrostatic shield
 Thermal sensors (PTC, PT100, Twin-blades)
 Regulation tabs
 Dual primary
 Inrush current, frequency, heating, ambient temperature, specific altitude
 Tropicalization
 Specific colour for the enclosure