



MCP 12500 - SINGLE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - 12,5KVA - IP00



SKU: 24443
 Référence technique: T12B44FDF0000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : single-phase
 Certification(s) : EN 60076
 Power : 12,5 kVA
 Primary voltage : 400V
 Secondary voltage : 230V
 :
 Protection : IP00
 Version : Transformer (regulation tabs $\pm 5\%$)
 Inrush current : less than or equal to 12 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 40°C
 No load losses : 105 W
 Load losses : 600 W
 Voltage drop : 4,6 %
 UCC : 5,2 %
 Efficiency : 94,7 %

DIMENSIONS:

Dimensions (A x B x H) : 330 x 265 x 470 mm
 Mounting centres (a x b) : 235 x 235 mm
 Mounting diameter (\emptyset) : 11x22 mm
 Weight : 56 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 1 x 32A
 :
 Secondary 230V (gG fuse(s)) : 1 x 63A
 Secondary 230V (C circuit breaker(s)) : 1 x 63A

OPTIONS:

Tropicalization
 Vibration isolating mount
 Runnig wheels