



MCP 20000 - SINGLE-PHASE TRANSFORMER 230/230V $\pm 5\%$ - ELECTROSTATIC SHIELD - 20KVA - IP00



SKU: 23464
Référence technique: T12B46DDF1000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : EN 60076
Power : 20 kVA
Primary voltage : 230V
Secondary voltage : 230V
:
Protection : IP00
Version : Transformer (electrostatic shield & regulation tabs $\pm 5\%$)
Inrush current : less than or equal to 8 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 170 W
Load losses : 870 W
Voltage drop : 4,2 %
UCC : 4,6 %
Efficiency : 95,1 %

DIMENSIONS:

Dimensions (A x B x H) : 330 x 370 x 530 mm
Mounting centres (a x b) : 235 x 340 mm
Mounting diameter (\emptyset) : 11x22 mm
Weight : 85 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 100A
Primary 230V (D circuit breaker) : 1 x 100A
:
Secondary 230V (gG fuse(s)) : 1 x 100A
Secondary 230V (C circuit breaker(s)) : 1 x 100A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels