



## MCP 25000 - SINGLE-PHASE TRANSFORMER 230/230V $\pm 5\%$ - 25KVA - IP00



SKU: 23473  
 Référence technique: T12B47DDF0000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : single-phase  
 Certification(s) : EN 60076  
 Power : 25 kVA  
 Primary voltage : 230V  
 Secondary voltage : 230V  
 :  
 Protection : IP00  
 Version : Transformer (regulation tabs  $\pm 5\%$ )  
 Inrush current : less than or equal to 8 In  
 Heatings : H (IEC 60085)  
 Max. ambient T° : 40°C  
 No load losses : 215 W  
 Load losses : 955 W  
 Voltage drop : 3,7 %  
 UCC : 4,1 %  
 Efficiency : 95,5 %

### DIMENSIONS:

Dimensions (A x B x H) : 330 x 370 x 530 mm  
 Mounting centres (a x b) : 235 x 340 mm  
 Mounting diameter ( $\emptyset$ ) : 11x22 mm  
 Weight : 98 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 125A  
 Primary 230V (D circuit breaker) : 1 x 125A  
 :  
 Secondary 230V (gG fuse(s)) : 1 x 125A  
 Secondary 230V (C circuit breaker(s)) : 1 x 125A

### OPTIONS:

Tropicalization  
 Vibration isolating mount  
 Runnig wheels