




## MCP 25000 - SINGLE-PHASE TRANSFORMER 400/230V - ELECTROSTATIC SHIELD - 25KVA - IP00



SKU: 24472  
Référence technique: T12B47FD01000



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : single-phase  
Certification(s) : EN 60076  
Power : 25 kVA  
Primary voltage : 400V  
Secondary voltage : 230V  
:  
Protection : IP00  
Version : Transformer (electrostatic shield)  
Inrush current : less than or equal to 8 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 40°C  
No load losses : 215 W  
Load losses : 955 W  
Voltage drop : 3,7 %  
UCC : 4,1 %  
Efficiency : 95,5 %

### DIMENSIONS:

Dimensions (A x B x H) : 330 x 370 x 530 mm  
Mounting centres (a x b) : 235 x 340 mm  
Mounting diameter (Ø) : 11x22 mm  
Weight : 98 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 1 x 63A  
:  
Secondary 230V (gG fuse(s)) : 1 x 125A  
Secondary 230V (C circuit breaker(s)) : 1 x 125A

### OPTIONS:

Tropicalization  
Vibration isolating mount  
Runnig wheels