


MCP 25000 - SINGLE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - ELECTROSTATIC SHIELD - 25KVA - IP00



SKU: 24474
 Référence technique: T12B47FDF1000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : single-phase
 Certification(s) : EN 60076
 Power : 25 kVA
 Primary voltage : 400V
 Secondary voltage : 230V
 :
 Protection : IP00
 Version : Transformer (electrostatic shield & regulation tabs $\pm 5\%$)
 Inrush current : less than or equal to 8 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 40°C
 No load losses : 215 W
 Load losses : 955 W
 Voltage drop : 3,7 %
 UCC : 4,1 %
 Efficiency : 95,5 %

DIMENSIONS:

Dimensions (A x B x H) : 330 x 370 x 530 mm
 Mounting centres (a x b) : 235 x 340 mm
 Mounting diameter (\emptyset) : 11x22 mm
 Weight : 98 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 1 x 63A
 :
 Secondary 230V (gG fuse(s)) : 1 x 125A
 Secondary 230V (C circuit breaker(s)) : 1 x 125A

OPTIONS:

Tropicalization
 Vibration isolating mount
 Runnig wheels