



MCP 31500 - SINGLE-PHASE TRANSFORMER 230/230V - ELECTROSTATIC SHIELD - 31,5KVA - IP00



SKU: 23482
 Référence technique: T12B48DD01000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : single-phase
 Certification(s) : EN 60076
 Power : 31,5 kVA
 Primary voltage : 230V
 Secondary voltage : 230V
 :
 Protection : IP00
 Version : Transformer (electrostatic shield)
 Inrush current : less than or equal to 8 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 40°C
 No load losses : 255 W
 Load losses : 1120 W
 Voltage drop : 3,4 %
 UCC : 4 %
 Efficiency : 95,8 %

DIMENSIONS:

Dimensions (A x B x H) : 330 x 370 x 580 mm
 Mounting centres (a x b) : 235 x 340 mm
 Mounting diameter (ø) : 11x22 mm
 Weight : 120 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 160A
 Primary 230V (D circuit breaker) : 1 x 160A
 :
 Secondary 230V (gG fuse(s)) : 1 x 160A
 Secondary 230V (C circuit breaker(s)) : 1 x 160A

OPTIONS:

Tropicalization
 Vibration isolating mount
 Runnig wheels