




MCP 31500 - ON REQUEST SINGLE-PHASE TRANSFORMER 31,5KVA - IP00



SKU: MCP31500_Specific
 Référence technique: T12B48...



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : single-phase
 Certification(s) : EN 60076
 Power : 31,5 kVA
 Primary voltage : max. 1000V
 Secondary voltage : max. 1000V
 :
 Protection : IP00
 Version : Transformer (specific)
 Inrush current : less than or equal to 8 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 40°C
 No load losses : 255 W
 Load losses : 1120 W
 Voltage drop : 3,4 %
 UCC : 4 %
 Efficiency : 95,8 %

DIMENSIONS:

Dimensions (A x B x H) : 330 x 370 x 580 mm
 Mounting centres (a x b) : 235 x 340 mm
 Mounting diameter (ø) : 11x22 mm
 Weight : 120 kg

PROTECTION(S) RECOMMANDÉE(S):

:
 Other voltages : N.C.

OPTIONS:

Electrostatic shield
 Thermal sensors (PTC, PT100, Twin-blades)
 Regulation tabs
 Dual primary
 Inrush current, frequency, heating, ambient temperature, specific altitude
 Tropicalization
 Vibration isolating mount
 Running wheels