



MCP 50000 - SINGLE-PHASE TRANSFORMER 230/230V ±5% - ELECTROSTATIC SHIELD - 50KVA - IP00



SKU: 23504
 Référence technique: T12B50DDF1000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : single-phase
 Certification(s) : EN 60076
 Power : 50 kVA
 Primary voltage : 230V
 Secondary voltage : 230V
 :
 Protection : IP00
 Version : Transformer (electrostatic shield & regulation tabs ±5%)
 Inrush current : less than or equal to 8 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 40°C
 No load losses : 265 W
 Load losses : 1400 W
 Voltage drop : 2,7 %
 UCC : 4 %
 Efficiency : 96,8 %

DIMENSIONS:

Dimensions (A x B x H) : 420 x 370 x 610 mm
 Mounting centres (a x b) : 280 x 340 mm
 Mounting diameter (ø) : 11x22 mm
 Weight : 173 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 230V (aM fuse) : 1 x 250A
 Primary 230V (D circuit breaker) : 1 x 250A
 :
 Secondary 230V (gG fuse(s)) : 1 x 250A
 Secondary 230V (C circuit breaker(s)) : 1 x 250A

OPTIONS:

Tropicalization
 Vibration isolating mount
 Runnig wheels