



MCPP 25000 - SINGLE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - ELECTROSTATIC SHIELD - 25KVA - IP21



SKU: 24478
Référence technique: T13B47FDF1000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : EN 60076
Power : 25 kVA
Primary voltage : 400V
Secondary voltage : 230V
:
Protection : IP21-IK08
Version : Transformer (electrostatic shield & regulation tabs $\pm 5\%$)
Inrush current : less than or equal to 8 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 215 W
Load losses : 955 W
Voltage drop : 3,7 %
UCC : 4,1 %
Efficiency : 95,5 %

DIMENSIONS:

Dimensions (A x B x H) : 610 x 470 x 770 mm
Mounting centres (a x b) : 235 x 440 mm
Mounting diameter (\varnothing) : 11x22 mm
Weight : 118 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 1 x 63A
:
Secondary 230V (gG fuse(s)) : 1 x 125A
Secondary 230V (C circuit breaker(s)) : 1 x 125A

OPTIONS:

Tropicalization
Vibration isolating mount
Runnig wheels
Factory assembled and wired primary and secondary protections
Specific colour for the enclosure