



MUS 5000 - SINGLE-PHASE TRANSFORMER (UL-CSA COMPATIBLE) - 5KVA - IP00



SKU: MUS5000_Specific
 Référence technique: 09F40...

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : single-phase
 Certification(s) : UL 5085-1, CSA C22.2
 Power : 5 kVA
 Primary voltage : max 600V
 Secondary voltage : max. 600V
 :
 Protection : IP00
 Version : specific compatible UL-CSA
 Inrush current : less than or equal to 25 I_n
 Heatings : 155°C
 Max. ambient T° : 40°C
 No load losses : 117 W
 Load losses : 166 W
 Voltage drop : 3,2 %
 UCC : 3,8 %
 Efficiency : 94,8 %

DIMENSIONS:

Dimensions (A x B x H) : 240 x 210 x 252 mm
 Mounting centres (a x b) : 200 x 168 mm
 Mounting diameter (ø) : 12x31 mm
 Weight : 39,3 kg

PROTECTION(S) RECOMMANDÉE(S):

:
 Other voltages : N.C.

OPTIONS:

Electrostatic shield
 Thermal sensors (PTC, PT100, Twin-blades)
 Regulation tabs
 Dual primary
 Inrush current, frequency, heating, ambient temperature, specific altitude
 Tropicalization