




MUSP 2000 - SINGLE-PHASE TRANSFORMER (UL-CSA COMPATIBLE) - 2KVA - IP21



SKU: MUSP2000_Specific
 Référence technique: 10F35...

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : single-phase
 Certification(s) : UL 5085-1, CSA C22.2
 Power : 2 kVA
 Primary voltage : max 600V
 Secondary voltage : max. 600V
 :
 Protection : IP41-IK08
 Version : specific compatible UL-CSA
 Inrush current : less than or equal to 25 In
 Heatings : 130°C
 Max. ambient T° : 40°C
 No load losses : 60 W
 Load losses : 74,3 W
 Voltage drop : 3,6 %
 UCC : 3,7 %
 Efficiency : 93,7 %

DIMENSIONS:

Dimensions (A x B x H) : 300 x 290 x 300 mm
 Mounting centres (a x b) : 250 x 274 mm
 Mounting diameter (ø) : 7x14 mm
 Weight : 28 kg

PROTECTION(S) RECOMMANDÉE(S):

:
 Other voltages : N.C.

OPTIONS:

Electrostatic shield
 Thermal sensors (PTC, PT100, Twin-blades)
 Regulation tabs
 Dual primary
 Inrush current, frequency, heating, ambient temperature, specific altitude
 Tropicalization
 Specific colour for the enclosure