




MUSP 40 - SINGLE-PHASE TRANSFORMER (UL-CSA COMPATIBLE) - 40VA - IP21



SKU: MUSP40_Specific
 Référence technique: 10F14...

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : single-phase
 Certification(s) : UL 5085-1, CSA C22.2
 Power : 40 VA
 Primary voltage : max 600V
 Secondary voltage : max. 600V
 :
 Protection : IP41-IK08
 Version : specific compatible UL-CSA
 Inrush current : less than or equal to 25 In
 Heatings : 105°C
 Max. ambient T° : 40°C
 No load losses : 3,5 W
 Load losses : 4,23 W
 Voltage drop : 9,6 %
 UCC : 9,5 %
 Efficiency : 83,8 %

DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm
 Mounting centres (a x b) : 200 x 224 mm
 Mounting diameter (ø) : 7x14 mm
 Weight : 4,2 kg

PROTECTION(S) RECOMMANDÉE(S):

:
 Other voltages : N.C.

OPTIONS:

Electrostatic shield
 Thermal sensors (PTC, PT100, Twin-blades)
 Regulation tabs
 Dual primary
 Inrush current, frequency, heating, ambient temperature, specific altitude
 Tropicalization
 Specific colour for the enclosure