



MUSP 500 - SINGLE-PHASE TRANSFORMER (UL-CSA COMPATIBLE) - 500VA - IP21



SKU: MUSP500_Specific
Référence technique: 10F27...



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : single-phase
Certification(s) : UL 5085-1, CSA C22.2
Power : 500 VA
Primary voltage : max 600V
Secondary voltage : max. 600V
:
Protection : IP41-IK08
Version : specific compatible UL-CSA
Inrush current : less than or equal to 25 In
Heatings : 105°C
Max. ambient T° : 40°C
No load losses : 26,5 W
Load losses : 17,2 W
Voltage drop : 3,3 %
UCC : 3,3 %
Efficiency : 91,9 %

DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm
Mounting centres (a x b) : 200 x 224 mm
Mounting diameter (ø) : 7x14 mm
Weight : 12,4 kg

PROTECTION(S) RECOMMANDÉE(S):

:
Other voltages : N.C.

OPTIONS:

Electrostatic shield
Thermal sensors (PTC, PT100, Twin-blades)
Regulation tabs
Dual primary
Inrush current, frequency, heating, ambient temperature, specific altitude
Tropicalization
Specific colour for the enclosure