




TP 100 - THREE-PHASE TRANSFORMER 400/400V ±5% - ELECTROSTATIC SHIELD - 100VA - IP00



SKU: 31184
 Référence technique: 28M18FFF1000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 61558-2-1
 Power : 100 VA
 Primary voltage : 400V
 Secondary voltage : 400V (Y+N)
 :
 Protection : IP00
 Version : with electrostatic shield & regulation tabs ±5%
 Inrush current : less than or equal to 25 I_n
 Heatings : B (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 4,1 W
 Load losses : 14,3 W
 Voltage drop : 12,5 %
 UCC : 10,5 %
 Efficiency : 84,5 %

DIMENSIONS:

Dimensions (A x B x H) : 120 x 61 x 125 mm
 Mounting centres (a x b) : 100 x 42 mm
 Mounting diameter (∅) : 6x13 mm
 Weight : 2,3 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 0,5A
 :
 Secondary 400V (gG fuse(s)) : 4 x 0,16A
 Secondary 400V (C circuit breaker(s)) : 4 x 0,16A

OPTIONS:

Tropicalization