





## TP 100 - THREE-PHASE TRANSFORMER 400/230V - ELECTROSTATIC SHIELD - 100VA - IP00



SKU: 32182  
 Référence technique: 28M18FD01000



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 61558-2-1  
 Power : 100 VA  
 Primary voltage : 400V  
 Secondary voltage : 230V (Y+N)  
 :  
 Protection : IP00  
 Version : with electrostatic shield  
 Inrush current : less than or equal to 25 I<sub>n</sub>  
 Heatings : B (IEC 60085)  
 Max. ambient T° : 35°C  
 No load losses : 4,1 W  
 Load losses : 14,3 W  
 Voltage drop : 12,5 %  
 UCC : 10,5 %  
 Efficiency : 84,5 %

### DIMENSIONS:

Dimensions (A x B x H) : 120 x 61 x 125 mm  
 Mounting centres (a x b) : 100 x 42 mm  
 Mounting diameter (∅) : 6x13 mm  
 Weight : 2,3 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 0,5A  
 :  
 Secondary 230V (gG fuse(s)) : 4 x 0,25A  
 Secondary 230V (C circuit breaker(s)) : 4 x 0,25A

### OPTIONS:

Tropicalization