




TP 100 - THREE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - 100VA - IP00



SKU: 32183
Référence technique: 28M18FDF0000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 61558-2-1
Power : 100 VA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP00
Version : with regulation tabs $\pm 5\%$
Inrush current : less than or equal to $25 I_n$
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 4,1 W
Load losses : 14,3 W
Voltage drop : 12,5 %
UCC : 10,5 %
Efficiency : 84,5 %

DIMENSIONS:

Dimensions (A x B x H) : 120 x 61 x 125 mm
Mounting centres (a x b) : 100 x 42 mm
Mounting diameter (\emptyset) : 6x13 mm
Weight : 2,3 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 0,5A
:
Secondary 230V (gG fuse(s)) : 4 x 0,25A
Secondary 230V (C circuit breaker(s)) : 4 x 0,25A

OPTIONS:

Tropicalization