



**TP 1000 - THREE-PHASE
TRANSFORMER 400/400V $\pm 5\%$ -
ELECTROSTATIC SHIELD - 1000VA -
IP00**



SKU: 31314
Référence technique: 28M31FFF1000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 61558-2-1
Power : 1000 VA
Primary voltage : 400V
Secondary voltage : 400V (Y+N)
:
Protection : IP00
Version : with electrostatic shield & regulation tabs $\pm 5\%$
Inrush current : less than or equal to 25 I_n
Heatings : F (IEC 60085)
Max. ambient T° : 35°C
No load losses : 26 W
Load losses : 73 W
Voltage drop : 6,8 %
UCC : 5 %
Efficiency : 91 %

DIMENSIONS:

Dimensions (A x B x H) : 180 x 150 x 175 mm
Mounting centres (a x b) : 150 x 95 mm
Mounting diameter (\emptyset) : 8x18 mm
Weight : 11,7 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 0,15A
:
Secondary 400V (gG fuse(s)) : 4 x 1,6A
Secondary 400V (C circuit breaker(s)) : 4 x 1,6A

OPTIONS:

Tropicalization