





TP 1000 - ON REQUEST THREE-PHASE TRANSFORMER 1000VA - IP00



SKU: TP1000_Specific
Référence technique: 28M31...

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 61558-2-1
Power : 1000 VA
Primary voltage : max. 1000V
Secondary voltage : max. 1000V
:
Protection : IP00
Version : specific
Inrush current : less than or equal to 25 In
Heatings : F (IEC 60085)
Max. ambient T° : 35°C
No load losses : 26 W
Load losses : 73 W
Voltage drop : 6,8 %
UCC : 5 %
Efficiency : 91 %

DIMENSIONS:

Dimensions (A x B x H) : 180 x 150 x 175 mm
Mounting centres (a x b) : 150 x 95 mm
Mounting diameter (∅) : 8x18 mm
Weight : 11,7 kg

PROTECTION(S) RECOMMANDÉE(S):

:
Other voltages : N.C.

OPTIONS:

Electrostatic shield
Thermal sensors (PTC, PT100, Twin-blades)
Regulation tabs
Primary and/or secondary coupling (star, delta, zig-zag)
Dual primary
Inrush current, frequency, heating, ambient temperature, specific altitude
Tropicalization