



**TP 1250 - THREE-PHASE
TRANSFORMER 400/400V \pm 5% -
1250VA - IP00**



SKU: 31323
Référence technique: 28M32FFF0000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 61558-2-1
Power : 1250 VA
Primary voltage : 400V
Secondary voltage : 400V (Y+N)
:
Protection : IP00
Version : with regulation tabs \pm 5%
Inrush current : less than or equal to 25 In
Heatings : F (IEC 60085)
Max. ambient T° : 35°C
No load losses : 33 W
Load losses : 80 W
Voltage drop : 6 %
UCC : 4,4 %
Efficiency : 91,8 %

DIMENSIONS:

Dimensions (A x B x H) : 180 x 165 x 175 mm
Mounting centres (a x b) : 150 x 110 mm
Mounting diameter (\emptyset) : 8x18 mm
Weight : 14 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 4A
:
Secondary 400V (gG fuse(s)) : 4 x 2A
Secondary 400V (C circuit breaker(s)) : 4 x 2A

OPTIONS:

Tropicalization