





**TP 1250 - THREE-PHASE  
TRANSFORMER 400/230V  $\pm 5\%$  -  
ELECTROSTATIC SHIELD - 1250VA -  
IP00**



SKU: 32324  
Référence technique: 28M32FDF1000



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 61558-2-1  
Power : 1250 VA  
Primary voltage : 400V  
Secondary voltage : 230V (Y+N)  
:  
Protection : IP00  
Version : with electrostatic shield & regulation tabs  $\pm 5\%$   
Inrush current : less than or equal to 25  $I_n$   
Heatings : F (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 33 W  
Load losses : 80 W  
Voltage drop : 6 %  
UCC : 4,4 %  
Efficiency : 91,8 %

### DIMENSIONS:

Dimensions (A x B x H) : 180 x 165 x 175 mm  
Mounting centres (a x b) : 150 x 110 mm  
Mounting diameter ( $\emptyset$ ) : 8x18 mm  
Weight : 14 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 4A  
:  
Secondary 230V (gG fuse(s)) : 4 x 3,15A  
Secondary 230V (C circuit breaker(s)) : 4 x 3,15A

### OPTIONS:

Tropicalization