






TP 160 - THREE-PHASE TRANSFORMER 400/230V - ELECTROSTATIC SHIELD - 160VA - IP00



SKU: 32212
Référence technique: 28M21FD01000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 61558-2-1
Power : 160 VA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP00
Version : with electrostatic shield
Inrush current : less than or equal to 25 I_n
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 5,8 W
Load losses : 20 W
Voltage drop : 11,1 %
UCC : 9,3 %
Efficiency : 86,1 %

DIMENSIONS:

Dimensions (A x B x H) : 120 x 70 x 125 mm
Mounting centres (a x b) : 100 x 51 mm
Mounting diameter (∅) : 6x13 mm
Weight : 3,1 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 0,5A
:
Secondary 230V (gG fuse(s)) : 4 x 0,4A
Secondary 230V (C circuit breaker(s)) : 4 x 0,4A

OPTIONS:

Tropicalization