




**TP 160 - THREE-PHASE TRANSFORMER  
 400/230V - ELECTROSTATIC SHIELD -  
 160VA - IP00**



SKU: 32212  
 Référence technique: 28M21FD01000



**CARACTÉRISTIQUES TECHNIQUES:**

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 61558-2-1  
 Power : 160 VA  
 Primary voltage : 400V  
 Secondary voltage : 230V (Y+N)  
 :  
 Protection : IP00  
 Version : with electrostatic shield  
 Inrush current : less than or equal to 25 I<sub>n</sub>  
 Heatings : B (IEC 60085)  
 Max. ambient T° : 35°C  
 No load losses : 5,8 W  
 Load losses : 20 W  
 Voltage drop : 11,1 %  
 UCC : 9,3 %  
 Efficiency : 86,1 %

**DIMENSIONS:**

Dimensions (A x B x H) : 120 x 70 x 125 mm  
 Mounting centres (a x b) : 100 x 51 mm  
 Mounting diameter (∅) : 6x13 mm  
 Weight : 3,1 kg

**PROTECTION(S) RECOMMANDÉE(S):**

Primary 400V (aM fuse(s)) : 3 x 0,5A  
 :  
 Secondary 230V (gG fuse(s)) : 4 x 0,4A  
 Secondary 230V (C circuit breaker(s)) : 4 x 0,4A

**OPTIONS:**

Tropicalization