



## TP 160 - THREE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - ELECTROSTATIC SHIELD - 160VA - IP00



SKU: 32214  
Référence technique: 28M21FDF1000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 61558-2-1  
Power : 160 VA  
Primary voltage : 400V  
Secondary voltage : 230V (Y+N)  
:  
Protection : IP00  
Version : with electrostatic shield & regulation tabs  $\pm 5\%$   
Inrush current : less than or equal to 25 In  
Heatings : B (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 5,8 W  
Load losses : 20 W  
Voltage drop : 11,1 %  
UCC : 9,3 %  
Efficiency : 86,1 %

### DIMENSIONS:

Dimensions (A x B x H) : 120 x 70 x 125 mm  
Mounting centres (a x b) : 100 x 51 mm  
Mounting diameter ( $\emptyset$ ) : 6x13 mm  
Weight : 3,1 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 0,5A  
:  
Secondary 230V (gG fuse(s)) : 4 x 0,4A  
Secondary 230V (C circuit breaker(s)) : 4 x 0,4A

### OPTIONS:

Tropicalization