





**TP 1600 - THREE-PHASE  
 TRANSFORMER 400/400V ±5% -  
 ELECTROSTATIC SHIELD - 1600VA -  
 IP00**



SKU: 31344  
 Référence technique: 28M34FFF1000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 61558-2-1  
 Power : 1600 VA  
 Primary voltage : 400V  
 Secondary voltage : 400V (Y+N)  
 :  
 Protection : IP00  
 Version : with electrostatic shield & regulation tabs ±5%  
 Inrush current : less than or equal to 25 I<sub>n</sub>  
 Heatings : F (IEC 60085)  
 Max. ambient T° : 35°C  
 No load losses : 39 W  
 Load losses : 103 W  
 Voltage drop : 6,1 %  
 UCC : 4,5 %  
 Efficiency : 91,8 %

### DIMENSIONS:

Dimensions (A x B x H) : 240 x 120 x 230 mm  
 Mounting centres (a x b) : 200 x 90 mm  
 Mounting diameter (∅) : 8x18 mm  
 Weight : 17 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 5A  
 :  
 Secondary 400V (gG fuse(s)) : 4 x 2,5A  
 Secondary 400V (C circuit breaker(s)) : 4 x 2,5A

### OPTIONS:

Tropicalization