





**TP 1600 - THREE-PHASE
 TRANSFORMER 400/400V ±5% -
 ELECTROSTATIC SHIELD - 1600VA -
 IP00**



SKU: 31344
 Référence technique: 28M34FFF1000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 61558-2-1
 Power : 1600 VA
 Primary voltage : 400V
 Secondary voltage : 400V (Y+N)
 :
 Protection : IP00
 Version : with electrostatic shield & regulation tabs ±5%
 Inrush current : less than or equal to 25 I_n
 Heatings : F (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 39 W
 Load losses : 103 W
 Voltage drop : 6,1 %
 UCC : 4,5 %
 Efficiency : 91,8 %

DIMENSIONS:

Dimensions (A x B x H) : 240 x 120 x 230 mm
 Mounting centres (a x b) : 200 x 90 mm
 Mounting diameter (∅) : 8x18 mm
 Weight : 17 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 5A
 :
 Secondary 400V (gG fuse(s)) : 4 x 2,5A
 Secondary 400V (C circuit breaker(s)) : 4 x 2,5A

OPTIONS:

Tropicalization