




**TP 1600 - THREE-PHASE  
TRANSFORMER 400/230V -  
ELECTROSTATIC SHIELD - 1600VA -  
IP00**



SKU: 32342  
Référence technique: 28M34FD01000



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 61558-2-1  
Power : 1600 VA  
Primary voltage : 400V  
Secondary voltage : 230V (Y+N)  
:  
Protection : IP00  
Version : with electrostatic shield  
Inrush current : less than or equal to 25 I<sub>n</sub>  
Heatings : F (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 39 W  
Load losses : 103 W  
Voltage drop : 6,1 %  
UCC : 4,5 %  
Efficiency : 91,8 %

### DIMENSIONS:

Dimensions (A x B x H) : 240 x 120 x 230 mm  
Mounting centres (a x b) : 200 x 90 mm  
Mounting diameter (∅) : 8x18 mm  
Weight : 17 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 5A  
:  
Secondary 230V (gG fuse(s)) : 4 x 4A  
Secondary 230V (C circuit breaker(s)) : 4 x 4A

### OPTIONS:

Tropicalization