





TP 1600 - ON REQUEST THREE-PHASE TRANSFORMER 1600VA - IP00



SKU: TP1600_Specific
 Référence technique: 28M34...



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 61558-2-1
 Power : 1600 VA
 Primary voltage : max. 1000V
 Secondary voltage : max. 1000V
 :
 Protection : IP00
 Version : specific
 Inrush current : less than or equal to 25 In
 Heatings : F (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 39 W
 Load losses : 103 W
 Voltage drop : 6,1 %
 UCC : 4,5 %
 Efficiency : 91,8 %

DIMENSIONS:

Dimensions (A x B x H) : 240 x 120 x 230 mm
 Mounting centres (a x b) : 200 x 90 mm
 Mounting diameter (∅) : 8x18 mm
 Weight : 17 kg

PROTECTION(S) RECOMMANDÉE(S):

:
 Other voltages : N.C.

OPTIONS:

Electrostatic shield
 Thermal sensors (PTC, PT100, Twin-blades)
 Regulation tabs
 Primary and/or secondary coupling (star, delta, zig-zag)
 Dual primary
 Inrush current, frequency, heating, ambient temperature, specific altitude
 Tropicalization