





TP 160 - ON REQUEST THREE-PHASE TRANSFORMER 160VA - IP00



SKU: TP160_Specific
Référence technique: 28M21...

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 61558-2-1
Power : 160 VA
Primary voltage : max. 1000V
Secondary voltage : max. 1000V
:
Protection : IP00
Version : specific
Inrush current : less than or equal to 25 In
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 5,8 W
Load losses : 20 W
Voltage drop : 11,1 %
UCC : 9,3 %
Efficiency : 86,1 %

DIMENSIONS:

Dimensions (A x B x H) : 120 x 70 x 125 mm
Mounting centres (a x b) : 100 x 51 mm
Mounting diameter (∅) : 6x13 mm
Weight : 3,1 kg

PROTECTION(S) RECOMMANDÉE(S):

:
Other voltages : N.C.

OPTIONS:

Electrostatic shield
Thermal sensors (PTC, PT100, Twin-blades)
Regulation tabs
Primary and/or secondary coupling (star, delta, zig-zag)
Dual primary
Inrush current, frequency, heating, ambient temperature, specific altitude
Tropicalization