





## TP 160 - ON REQUEST THREE-PHASE TRANSFORMER 160VA - IP00



SKU: TP160\_Specific  
Référence technique: 28M21...



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 61558-2-1  
Power : 160 VA  
Primary voltage : max. 1000V  
Secondary voltage : max. 1000V  
:  
Protection : IP00  
Version : specific  
Inrush current : less than or equal to 25 In  
Heatings : B (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 5,8 W  
Load losses : 20 W  
Voltage drop : 11,1 %  
UCC : 9,3 %  
Efficiency : 86,1 %

### DIMENSIONS:

Dimensions (A x B x H) : 120 x 70 x 125 mm  
Mounting centres (a x b) : 100 x 51 mm  
Mounting diameter (∅) : 6x13 mm  
Weight : 3,1 kg

### PROTECTION(S) RECOMMANDÉE(S):

:  
Other voltages : N.C.

### OPTIONS:

Electrostatic shield  
Thermal sensors (PTC, PT100, Twin-blades)  
Regulation tabs  
Primary and/or secondary coupling (star, delta, zig-zag)  
Dual primary  
Inrush current, frequency, heating, ambient temperature, specific altitude  
Tropicalization