





**TP 200 - THREE-PHASE TRANSFORMER  
400/400V - ELECTROSTATIC SHIELD -  
200VA - IP00**



SKU: 31222

Référence technique: 28M22FF01000



### **CARACTÉRISTIQUES TECHNIQUES:**

Type : Transformer  
Current : three-phase  
Certification(s) : EN 61558-2-1  
Power : 200 VA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP00  
Version : with electrostatic shield  
Inrush current : less than or equal to 25 I<sub>n</sub>  
Heatings : B (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 7,8 W  
Load losses : 20,9 W  
Voltage drop : 9,5 %  
UCC : 7,9 %  
Efficiency : 87,5 %

### **DIMENSIONS:**

Dimensions (A x B x H) : 120 x 80 x 125 mm  
Mounting centres (a x b) : 100 x 61 mm  
Mounting diameter (∅) : 6x13 mm  
Weight : 3,7 kg

### **PROTECTION(S) RECOMMANDÉE(S):**

Primary 400V (aM fuse(s)) : 3 x 0,63A  
:  
Secondary 400V (gG fuse(s)) : 4 x 0,315A  
Secondary 400V (C circuit breaker(s)) : 4 x 0,315A

### **OPTIONS:**

Tropicalization