





**TP 200 - THREE-PHASE TRANSFORMER
400/400V ±5% - ELECTROSTATIC
SHIELD - 200VA - IP00**



SKU: 31224

Référence technique: 28M22FFF1000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 61558-2-1
Power : 200 VA
Primary voltage : 400V
Secondary voltage : 400V (Y+N)
:
Protection : IP00
Version : with electrostatic shield & regulation tabs ±5%
Inrush current : less than or equal to 25 In
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 7,8 W
Load losses : 20,9 W
Voltage drop : 9,5 %
UCC : 7,9 %
Efficiency : 87,5 %

DIMENSIONS:

Dimensions (A x B x H) : 120 x 80 x 125 mm
Mounting centres (a x b) : 100 x 61 mm
Mounting diameter (∅) : 6x13 mm
Weight : 3,7 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 0,63A
:
Secondary 400V (gG fuse(s)) : 4 x 0,315A
Secondary 400V (C circuit breaker(s)) : 4 x 0,315A

OPTIONS:

Tropicalization