




**TP 200 - THREE-PHASE TRANSFORMER
 400/230V - ELECTROSTATIC SHIELD -
 200VA - IP00**



SKU: 32222
 Référence technique: 28M22FD01000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 61558-2-1
 Power : 200 VA
 Primary voltage : 400V
 Secondary voltage : 230V (Y+N)
 :
 Protection : IP00
 Version : with electrostatic shield
 Inrush current : less than or equal to 25 I_n
 Heatings : B (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 7,8 W
 Load losses : 20,9 W
 Voltage drop : 9,5 %
 UCC : 7,9 %
 Efficiency : 87,5 %

DIMENSIONS:

Dimensions (A x B x H) : 120 x 80 x 125 mm
 Mounting centres (a x b) : 100 x 61 mm
 Mounting diameter (∅) : 6x13 mm
 Weight : 3,7 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 0,63A
 :
 Secondary 230V (gG fuse(s)) : 4 x 0,5A
 Secondary 230V (C circuit breaker(s)) : 4 x 0,5A

OPTIONS:

Tropicalization