



## TP 2000 - THREE-PHASE TRANSFORMER 400/230V - ELECTROSTATIC SHIELD - 2KVA - IP00



SKU: 32352  
Référence technique: 28M35FD01000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 61558-2-1  
Power : 2 kVA  
Primary voltage : 400V  
Secondary voltage : 230V (Y+N)  
:  
Protection : IP00  
Version : with electrostatic shield  
Inrush current : less than or equal to 25 In  
Heatings : F (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 47 W  
Load losses : 112 W  
Voltage drop : 5,3 %  
UCC : 3,9 %  
Efficiency : 92,6 %

### DIMENSIONS:

Dimensions (A x B x H) : 240 x 130 x 230 mm  
Mounting centres (a x b) : 200 x 100 mm  
Mounting diameter (ø) : 8x18 mm  
Weight : 20 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 6,3A  
:  
Secondary 230V (gG fuse(s)) : 4 x 5A  
Secondary 230V (C circuit breaker(s)) : 4 x 5A

### OPTIONS:

Tropicalization