



**TP 2000 - THREE-PHASE
 TRANSFORMER 400/230V ±5% -
 ELECTROSTATIC SHIELD - 2KVA - IP00**



SKU: 32354
 Référence technique: 28M35FDF1000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 61558-2-1
 Power : 2 kVA
 Primary voltage : 400V
 Secondary voltage : 230V (Y+N)
 :
 Protection : IP00
 Version : with electrostatic shield & regulation tabs ±5%
 Inrush current : less than or equal to 25 In
 Heatings : F (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 47 W
 Load losses : 112 W
 Voltage drop : 5,3 %
 UCC : 3,9 %
 Efficiency : 92,6 %

DIMENSIONS:

Dimensions (A x B x H) : 240 x 130 x 230 mm
 Mounting centres (a x b) : 200 x 100 mm
 Mounting diameter (∅) : 8x18 mm
 Weight : 20 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 6,3A
 :
 Secondary 230V (gG fuse(s)) : 4 x 5A
 Secondary 230V (C circuit breaker(s)) : 4 x 5A

OPTIONS:

Tropicalization