





TP 250 - THREE-PHASE TRANSFORMER 400/400V $\pm 5\%$ - 250VA - IP00



SKU: 31233
Référence technique: 28M23FFF0000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 61558-2-1
Power : 250 VA
Primary voltage : 400V
Secondary voltage : 400V (Y+N)
:
Protection : IP00
Version : with regulation tabs $\pm 5\%$
Inrush current : less than or equal to 25 In
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 9,4 W
Load losses : 23 W
Voltage drop : 8,4 %
UCC : 7 %
Efficiency : 88,5 %

DIMENSIONS:

Dimensions (A x B x H) : 150 x 119 x 150 mm
Mounting centres (a x b) : 125 x 62 mm
Mounting diameter (\emptyset) : 6x13 mm
Weight : 4,9 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 0,8A
:
Secondary 400V (gG fuse(s)) : 4 x 0,4A
Secondary 400V (C circuit breaker(s)) : 4 x 0,4A

OPTIONS:

Tropicalization